# LNP™ STAT-KON™ COMPOUND DE003Z

DC-1003 E
REGION ASIA

## DESCRIPTION

LNP STAT-KON* DE003Z is a compound based on Polycarbonate resin containing 15% Carbon Fiber. Added features of this material include: Electrically Conductive, Extrusion Grade.

## TYPICAL PROPERTY VALUES

Revision 20190107

| PROPERTIES | TYPICAL VALUES | UNITS | TEST METHODS |
|---|---|---|---|
| **IMPACT** | | | |
| **Instrumented Impact Energy @ peak, 23°C** | 15 | J | ASTM D 3763 |
| **Multiaxial Impact** | 104 | J | ISO 6603 |
| **THERMAL** | | | |
| **HDT, 1.82 MPa, 3.2mm, unannealed** | 144 | °C | ASTM D 648 |
| **HDT/Af, 1.8 MPa Flatw 80*10*4 sp=64mm** | 143 | °C | ISO 75/Af |

## DISCLAIMER

Any sale by SABIC, its subsidiaries and affiliates (each a "seller"), is made exclusively under seller's standard conditions of sale (available upon request) unless agreed otherwise in writing and signed on behalf of the seller. While the information contained herein is given in good faith, SELLER MAKES NO WARRANTY, EXPRESS OR IMPLIED, INCLUDING MERCHANTABILITY AND NONINFRINGEMENT OF INTELLECTUAL PROPERTY, NOR ASSUMES ANY LIABILITY, DIRECT OR INDIRECT, WITH RESPECT TO THE PERFORMANCE, SUITABILITY OR FITNESS FOR INTENDED USE OR PURPOSE OF THESE PRODUCTS IN ANY APPLICATION. Each customer must determine the suitability of seller materials for the customer's particular use through appropriate testing and analysis. No statement by seller concerning a possible use of any product, service or design is intended, or should be construed, to grant any license under any patent or other intellectual property right.

© 2019 Copyright by SABIC. All rights reserved